

CLEAN VERSION OF ALL PENDING CLAIMS

~~9. A method for extending the operating life of a fixed bed reactor for reacting a feedstock said fixed bed reactor comprising a fixed catalyst bed having a top and a bottom layer, wherein during operation of said fixed bed reactor a feedstock flow passes through said fixed catalyst bed and a pressure drop across said top layer of said fixed catalyst bed increases during reaction of said feedstock due to fouling of said top layer of said fixed catalyst bed, the method comprising:~~

~~(a) placing a bypass apparatus within said fixed catalyst bed in substantial alignment with said feedstock flow through said fixed catalyst bed said bypass apparatus comprising,~~

~~a cage member comprising a first elongated hollow member having a top wall, side walls and a bottom wall, said cage member having openings therein, and~~

~~a second hollow elongated member for bypassing an increasing amount of said feedstock through said second hollow elongated member into said cage member as said top layer of said fixed bed fouls to create a bypass flow, said second hollow elongated member being disposed within said cage member and protruding through said top wall of said cage member and wherein said second hollow elongated member extends above said fixed catalyst bed through said cage member, said second hollow elongated member being sized to regulate said bypass flow, said cage member having a substantially larger cross-section than said second hollow elongated member to effectively reduce the velocity of said bypass flow as it exits from said cage member into said bottom layer of said fixed catalyst bed,~~

~~(b) introducing said feedstock into said fixed bed of catalytic material, wherein a majority of said feedstock will flow through said top layer of said fixed bed of catalytic material, and~~

~~(c) as said top layer of said fixed bed of catalytic material fouls, bypassing said increasing amount of said feedstock to said bottom layer of said fixed bed of catalytic material;~~

~~wherein said second hollow elongated member is continuously open to said bypass flow.~~

CLEAN VERSION OF ALL PENDING CLAIMS (continued)

E2 10. The method of claim 9, wherein said hydrocarbon feed is selected from the group consisting of liquid feed, vapor feed, and mixtures thereof.

E3 11. The method of claim 9, wherein said feedstock is selected from the group consisting of hydrocarbon feedstocks, chemical feedstocks, and mixtures thereof.

1 12. A method for extending an operating life of a fixed catalyst bed reactor, the method comprising:

providing a reactor comprising at least one fixed catalyst bed;

E4 5 establishing a feedstock flow through said at least one fixed catalyst bed partitioning said at least one fixed catalyst bed into a top layer and a bottom layer by placing a bypass apparatus within said at least one fixed catalyst bed in substantial alignment with said flow of said feedstock, said bypass apparatus comprising,

a cage member comprising a first elongated hollow member having a top wall, side walls and a bottom wall, said cage member having openings therein, and

10 10 a second hollow elongated member for bypassing an increasing amount of said feedstock through said second hollow elongated member into said cage member as said top layer of said fixed bed fouls to create a bypass flow, said second hollow elongated member being disposed within said cage member and protruding through said top wall of said cage member and wherein said 15 second hollow elongated member extends above said at least one fixed catalyst bed through said cage member, said second hollow elongated member being sized to regulate said bypass flow of said feedstock into said cage, said cage having a substantially larger cross-section than said second hollow elongated member to effectively reduce the velocity of said bypass flow as it 20 exits from said cage member into said bottom layer of said at least one fixed 21 catalyst bed,

CLEAN VERSION OF ALL PENDING CLAIMS (continued)

E 4  
cont. 22 bypassing said increasing amount of said feedstock flow through said bypass apparatus to the bottom unfouled layer, as said top layer fouts;

wherein said second hollow elongated member is continuously opened to said bypass

25 flow.

14. The method of claim 12, wherein said second hollow elongated member is a tubular member having a diameter from about 0.25 to about 12 inches.

15. The method of claim 12, wherein said cage member is a tubular member having a diameter of about 3 to about 20 inches.

16. The method of claim 12, wherein said second hollow elongated member has a pressure drop of about 5 to about 50 times greater than that of said at least one fixed catalyst bed when said at least one fixed catalyst bed is a fresh catalyst bed.

E 5 17. The method of claim 12, wherein said bypass apparatus further comprises a separation device disposed above said second hollow elongated member.

18. The method of claim 12, wherein said separation device is selected from the group consisting of caps, centrifugal separators and cyclones.

19. The method of claim 12, wherein said at least one fixed catalyst bed contains packing material for distributing particulates passing through said bypass apparatus.

20. The method of claim 19, wherein said packing material is selected from the group consisting of catalyst particles, alumina balls, inert particles, inert packing and mixtures thereof.